

## Product Information

Double-sided mounting tape based on a polyethylene foam carrier.

The acrylic adhesive offers a high resistance against temperature, ageing and weathering with an excellent initial tack.

Combined with the permanent elastic foam carrier, POLI-MOUNT 3905 reaches a high final tack on rough and slightly uneven surfaces.

The tape reduces vibration and compensates different expansion rates between the substrates.

Especially to be emphasised are the following properties:

- Mounting of decorative trims, decals and logos especially in the aftermarket of the automotive industry.
- Mounting of plastic hooks, holders and dispensers.
- Mounting of cover plates and cable trunkings in the phono, household appliances and electrical industry.
- Mounting of objects at exhibitions and shop displays.
- Self-adhesive mounting of mirrors as well as aluminium and plexiglass facade coverings.

## Technical Data

<b>Carrier:</b>	PE-foam, black	
<b>Adhesive:</b>	Acrylic	
<b>Liner:</b>	PE-film, green	
<b>Adhesion [N/cm]:</b>	4,10	+/- 10 %
<b>Thickness [mm]:</b>	1,00	+/- 5 %
<b>Temperature resistance [°C]:</b>	-40 / +80	

## Standard Dimensions

1.240 mm x 50 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

### POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17  
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0  
Fax: +49 (0) 2642 – 9836 37

E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)  
Internet: [www.poli-tape.de](http://www.poli-tape.de)

28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.